

Mud & Silt Remover 25 l

Product Group: 652

Product number: 635326

General description

Mud & Silt Remover is a liquid compound. It keeps mud in suspension and cleans fouled systems completely. Mud & Silt Remover removes sediments, silt and mud from ballast tanks, cooling water systems, pipelines, etc.

Features

- No acids, alkali or solvent
- Biodegradable
- Non-toxic
- Non-flammable
- Keeps mud in suspension and cleans fouled systems
- Removes sediments, silt and mud from ballast tanks, cooling water systems, pipelines, etc.
- Inject in small quantities into the ballast or cooling water system to be cleaned

Benefits

- Effective and economical in use
-

Ordering information

Product number	Product name
635326	MUD & SILT REMOVER 25 LTR

Directions for use

Mud & Silt Remover removes sediments, silt and mud from ballast tanks, cooling water systems, pipelines, etc.

Mud & Silt Remover should be injected in small quantities into the ballast or cooling water of the system to be treated, prior to filling the tanks or the system. Heavy deposits may require several treatments.

Caution!

Spillages of Mud & Silt Remover should be avoided, as floors, decks, etc. will become very slippery. Clean as soon as possible.

NOTE: SHELF LIFE - 24 MONTHS FROM PRODUCTION

Dosing method

If product is regular dosed each time tanks are ballasted, a maintenance dosage of 2.5 Ltr/100 tonnes of ballast water is recommended. To clean heavy accumulation a dose rate of 10 Ltr Mud & Silt Remover per 100 tonnes of ballast water is recommended.

Inject Mud & Silt Remover preferably into the suction line of the ballast or cooling water pump, to ensure thorough mixing with the incoming water. If possible, circulate the water through the tanks and the suspended mud and silt will be pumped out when deballasting.

Documentation

SDS

- [MUD & SILT REMOVER 25 LTR](#)
-

Further Technical Data

Form Viscous liquid

Appearance White

Density 1,0

pH, in conc. 7-8